



Technical data:

- No. of contact: 64
- Termination method: Crimp termination
- Gender: Male
- Size: B24
- Conductor cross-section: 0.14 ... 2.5 mm<sup>2</sup>
- Rated current: 10A
- Rated voltage: 250V
- Rated impulse voltage: 4kV
- Pollution degree: 3
- Rated voltage acc.to UL: 600V
- Insulation resistance:  $\geq 10^9 \Omega$
- Contact resistance:  $\leq 3m\Omega$
- Limiting temperature: -40 ... +125°C
- Material(insert): Polycarbonate
- Color(insert): RAL 7032(pebble grey)
- Mating cycles:  $\geq 500$
- Material flammability class acc. to UL94: V-0
- RoHS: Compliant
- Specifications: IEC61984, EN60664-1

技术数据:

- 针数: 64
- 接线方式: 冷压接针
- 公母类型: 公头
- 尺寸: B24
- 导体截面积: 0.14 ... 2.5 mm<sup>2</sup>
- 额定电流: 10A
- 额定电压: 250V
- 额定脉冲电压: 4kV
- 污染等级: 3
- 额定电压符合UL: 600V
- 绝缘阻抗:  $\geq 10^9 \Omega$
- 接触电阻:  $\leq 3m\Omega$
- 极限温度: -40 ... +125°C
- 材料(插芯): 聚碳酸酯
- 颜色(插芯): RAL 7032(卵石灰)
- 插拔次数:  $\geq 500$
- 材料阻燃性等级符合UL94: V-0
- RoHS: 符合豁免标准
- 规格: IEC61984, EN60664-1

Panel cut out  
面板开孔尺寸

 <b>InKonn</b> <sup>®</sup> InKonn (Suzhou) Electric Technology Co.,Ltd.	 All Dimensions in mm Original Size DIN A4	Date 2019-05-14	Drawing No. TC8484474	Rev. A00	Scale 1:1
	Part No. 10 31 064 2100	Created by Shuxu Huang	Checked by Yiyi Luo	Page 1/1	
Type Name ID-064-CM					