


coding possibilities
with coding pin
可配合 编码

①		
②		
③		
④		
⑤		
⑥		



Technical data:	技术数据:
- No. of contact: 7	- 针数: 7
- Termination method: Crimp termination	- 接线方式: 冷压接针
- Gender: Male	- 公母类型: 公头
- Size: A3	- 尺寸: A3
- Conductor cross-section: 0.14 ... 2.5 mm ²	- 导体截面积: 0.14 ... 2.5 mm ²
- Rated current: 10A	- 额定电流: 10A
- Rated voltage: 400V	- 额定电压: 400V
- Rated impulse voltage: 6kV	- 额定脉冲电压: 6kV
- Pollution degree: 3	- 污染等级: 3
- Rated voltage acc.to UL: 600V	- 额定电压符合UL: 600V
- Insulation resistance: ≥10 ¹⁰ Ω	- 绝缘阻抗: ≥10 ¹⁰ Ω
- Limiting temperature: -40 ... +125°C	- 极限温度: -40 ... +125°C
- Material(insert): Polycarbonate	- 材料(插芯): 聚碳酸酯
- Color(insert): RAL 7032(pebble grey)	- 颜色(插芯): RAL 7032(卵石灰)
- Mating cycles: ≥500	- 插拔次数: ≥500
- Material flammability class acc. to UL94: V-0	- 材料阻燃性等级符合UL94: V-0
- RoHS: Compliant	- RoHS: 符合豁免标准
- Specifications: IEC61984, EN60664-1	- 规格: IEC61984, EN60664-1

	All Dimensions in mm Original Size DIN A4	Date 2019-07-18	Drawing No. TC2892228	Rev. A00	Scale 1:1
	Part No. 10 36 007 2100		Created by Han Lyu	Checked by Yiyi Luo	Page 1/1
Type Name IQ-007/0-CM					
InKonn (Suzhou) Electric Technology Co.,Ltd.					